





ASSA ABLOY Electronic Security Hardware

Securiton® Magnalock® Comparison

ASSA ABLOY
Opening Solutions

Experience a safer
and more open world

		ECOMAGS		DURABLE MAGS										SPECIALTY MAGS	
															
		Securiton M380E Series	Securiton M680E Series	Securiton iMXDA Delayed Egress	Securiton M32	Securiton M62	Securiton M82	Securiton M38	Securiton M68	Securiton DM62	Securiton M34R	Securiton SAM	Securiton SAM2-24	Securiton MM15 Memlock	Securiton M62FG-SASM Gate Lock
HOLDING FORCE		600 lbs	1,200 lbs	1,200 lbs	600 lbs	1,200 lbs	1,800 lbs	600 lbs	1,200 lbs	1,200 lbs	500 lbs	1,200 lbs	600 lbs	4,000 lbs	1,200 lbs
OUTDOOR RATED					✓	✓	✓								
DOOR APPLICATIONS	OUT-SWING DOOR														
	Glass Door (w/ Aluminum Frame)	✓	✓		✓	✓		✓	✓						
	Wood Door	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	
	Metal Door	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	
	IN-SWING DOOR														
	Glass Door (w/ Aluminum Frame)				✓	✓	✓	✓	✓						
	Wood Door				✓	✓	✓	✓	✓			✓	✓		
	Metal Door				✓	✓	✓	✓	✓			✓	✓	✓	
	SLIDING DOOR														
ELECTRICAL	Double Sliding Doors											✓	✓		
	Single Sliding Doors										✓	✓	✓		
SPECIFICATIONS	12 VDC Current Draw	140 mA*	113 mA*	370 mA	300 mA	250 mA	350 mA	350 mA	250 mA	250 mA	320 mA	320 mA		100 mA*	250 mA
	24 VDC Current Draw	90 mA*	52 mA*	270mA	150 mA	150 mA	200 mA	170 mA	125 mA	150 mA	170 mA	170 mA	84 mA	200 mA*	150 mA
	Dual Voltage 12/24 VDC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	UL 10C Fire Rated	1 Hour	1 Hour		1 Hour	1 Hour	1 Hour	1 Hour	1 Hour	1 Hour		1 Hour	1 Hour	1 Hour	1 Hour
	UL 294 Listed	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓		
	CAN4-S104 / CAN-ULC-S533 Listed	S104	S104	✓	✓	✓	✓	✓	✓		✓	✓	✓	S533	✓
FEATURES	California State Fire Marshal Listed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
	UL 1034 Listed Burglary-Resistant Listed	✓	✓												
	Patented BondSTAT magnetic bond sensor	✓	Optional	Included	Optional	Optional	Optional	SenSTAT Optional	SenSTAT Optional	Optional	Optional	Optional	Optional		Optional
	Integrated Door Position Switch	✓	✓		Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional		Optional	Optional
	Integrated REX	Optional	Optional												
	Anti-Tamper Switch	✓	✓					Optional	Optional					Optional	
	Additional Strike Plate Options				✓	✓	✓								✓
	Finish Options	9	9												
	Dress Cover Finish Options				✓	✓	✓							✓	

* Refer to catalog for additional information regarding electrical consumption.



MagnaCare
Warranty

All Securiton
Magnalocks
include

- Automatic dual-voltage uses 12 or 24 volt power supply and protects Magnalock
- World-class technical support experts, ready to assist you in selecting hardware, wiring and troubleshooting your opening
- Collapsing blind nuts securely anchor Magnalocks to the frame with up to 4,000 lbs of tensile strength
- Excellent product quality—Magnalocks are manufactured in an ISO9001 and ISO14001 certified factory in Phoenix, AZ
- MagnaCare®, the best warranty in the industry – lifetime replacement, no-fault, no questions asked